DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 40 N., R. 50 E., MDM, NEVADA

_		
	CHAINS	Descend 390 ft. over N. slope.
	59.50	Ravine, drains NNW.; desc. 240 ft. over broken W. slope.
	171.50	Spur, slopes NW.; desc. 110 ft. over broken NW. slope.
	183.01	Intersect the Eighth Standard Parallel North.
		Point for the closing corner of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
		Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
		T41N R50E <u>S 36</u> S 4]S 3 T40N R50E C C
		1974
		From this corner, the standard corner of secs. 35 and 36, bears N. 89° 36' W., 18.76 chs. dist.
		The point for the N. 4 sec. cor. of sec. 3, at proportionate distance and on the Eighth Standard Parallel North.
		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock and in a mound of stone, 6 ft. base to top, with brass cap mkd.
		14 S 3 T40N R50E
		1974
		From this corner, the standard \(\frac{1}{2} \) sec. cor. of sec. 36, bears N. 89° 36' W., 18.76 chs. dist.
	,	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.
		N. 0° 21' W., bet. secs. 32 and 33.
	: : :	Over mountainous land, covered with medium sagebrush and bunchgrass; asc. 270 ft. over W. slope changing to S. slope.
	37.40	Trail road, bears NNW. and SSE.
	40.79	The ¼ sec. cor. of secs. 32 and 33, monumented with a granite stone, 14x10x8 ins., firmly set in a mound of stone, mkd. ¼ on W. face.