CHADIC	DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY T. 38 N., R. 45 E.
chains 80.30	The cor. of secs. 2, 3, 34 and 35, monumented with a granite stone, 15x9x4 ins., mkd. with 4 grooves on the W. face and 2 grooves on the E. face, and firmly set in a mound of stone.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T39N R45E <u>S 34 S 35</u> S 3 S 2 T38N R45E
	1970
	bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LIN T. 38 N., R. 45 E., MOUNT DIABLO MERIDIAN, NEVADA.
	Reestablishment of a Portion of the Surveys Executed by U. S. Deputy Surveyors A. J. Hatch, J. C. Smyles and J. H. Eaton in 1873, and U. S. Deputy Surveyors McClellan and Bridges in 1885, and the Dependent Resurvey Executed by U. S. Surveyor W. T. Strover in 1911.
	The cor. of secs. 1, 2, 11 and 12, monumented with a basalt stone, 17x12x6 ins., marked with 5 grooves on the S. face and 1 groove on the E. face, and firmly set in a mound of stone.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T38N R45E <u>S 2 S 1</u> S 11 S 12
	1970
	bury the original cornerstone alongside the iron post.
	N. 0° 06' E., bet. secs. 1 and 2.
	Desc. 180 ft. over NW. slope to Evans Creek, through medium sagebrush.
0.40	Wash, 3 ft. deep, 10 lks. wide, drains WNW.

10