

TOWNSHIP 37 NORTH, RANGE 37 EAST

CHAINS

The geographic position for the southeast corner of the township is at latitude $41^{\circ} 01' 57.9''$ N. and longitude $117^{\circ} 45' 11.6''$ W., as adjusted along section lines from U.S.C. and G.S. triangulation station "NORTHWEST CORNER," which is the northwest corner of the City of Winnemucca, Nevada, and the corner of Secs. 13, 18, 19 and 24, Tps. 36 N., Rs. 37 and 38 E.

The magnetic declination was read at a number of stations throughout the township and the mean of these readings was found to be 18° East.

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 37 N., R. 37 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of the Survey Executed by
U. S. Deputy Surveyor William Epler
in 1867,
Dependently Resurveyed by
U. S. Deputy Surveyor H. B. Maxson
in 1888,
and Dependently Resurveyed by
U. S. Transitman A. T. Harris and
U. S. Surveyor T. A. Haigh
in 1913.

The cor. of Tps. 36 and 37 N., Rs. 37 and 38 E., monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record.

N. $0^{\circ} 36'$ W., bet. secs. 31 and 36.

Over rolling land, through sagebrush and bunchgrass; asc. 40 ft. over a SE. slope.

- 3.40 Spur, slopes E.; desc. 70 ft. over a NE. slope.
- 10.30 Draw, drains E.; asc. 30 ft. over a SE. slope.
- 15.60 Spur, slopes E.; desc. 170 ft. over a NE. slope.
- 39.59 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 31 and 36.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

WC
, T37N
R37E R38E
 $\frac{1}{4}$
S 36 \uparrow S 31
1971

set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.