

## DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 37 N., R. 37 E.

## CHAINS

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T37N  
R36E R37E  
S 24 | S 19  
S 25 | S 30

1970

bury the original cornerstone and set a steel fence post,  $5\frac{1}{2}$  ft. long,  $2\frac{1}{2}$  ft. in the ground, alongside the iron post and raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.

N.  $0^{\circ} 36'$  E., bet. secs. 19 and 24.

Over nearly level land, through sagebrush and bunchgrass.

26.80 Trail road, bears E. and W.

42.02 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.

T37N  
R36E R37E  
 $\frac{1}{4}$   
S 24 | S 19

1970

set a steel fence post,  $5\frac{1}{2}$  ft. long,  $2\frac{1}{2}$  ft. in the ground, alongside the iron post.

From this corner, the NE. corner of fence, at the mill site, bears S.  $5^{\circ} 06'$  W., 7.59 chs. dist.; fences, bear W. and S.

84.04 The cor. of secs. 13, 18, 19 and 24, monumented with a redwood post, 4x2 ins., 18 ins. long, dimly scribed and loosely set in a mound of earth.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap mkd.