

4

DEPENDENT RESURVEY OF A PORTION OF THE
FOURTH STANDARD PARALLEL NORTH, THROUGH RANGE 35 EAST, MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF
THE FOURTH STANDARD PARALLEL NORTH,
THROUGH RANGE 35 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
William Epler, U. S. Deputy Surveyor
in 1865

The standard cor. of Tps. 21 N., Rs. 35 and 36 E., monumented with a limestone, 6x12x16 ins., mkd. with 6 notches on the N., E. and W. edges, firmly set in a mound of stone, with a basalt stone, 14x16x36 ins., mkd. HRGM (Humboldt River Guide Meridian) on the N. and S. faces, firmly set alongside the limestone in the same mound of stone.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to bedrock and in a mound of stone, 6 ft. base to top, with brass cap mkd.

SC
T21N
R35E | R36E
S 36 | S 31

1970

deposit the original corner stone and the basalt stone alongside the iron post.

From this corner, the closing cor. of Tps. 20 N., Rs. 35 and 36 E., identical with the Nevada Planning Division of the Nevada Highway Department station "PIX," monumented with an iron post, 3 ins. diam., set, mkd. and witnessed as described in the official record, bears N. 89° 46' E., 4.29 chs. dist.

N. 89° 58' W., along the S. bdy. of sec. 36.

Over rolling hills; desc. 150 ft. along a S. slope, changing to a W. slope.

12.00 Wash, 10 lks. wide, 2 ft. deep, in ravine, drains NNW.; asc. 140 ft. over a NE. slope.

19.00 Top of ascent, slopes N.; desc. 210 ft. over a NW. slope.

39.77 The standard ¼ sec. cor. of sec. 36, monumented with a basalt stone, 8x10x27 ins., mkd. ¼ on the N. face, firmly set in a mound of stone.

At the corner point