

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 19 N., R. 37 E.

CHAINS	
36.20	Wash, 20 lks. wide, 2 ft. deep, drains SSE.; asc. 80 ft. over NE. slope.
39.80	<p>The cor. of secs. 31 and 32, monumented with a granite stone, 18x12x4 ins., firmly set in the ground, mkd. with 5 grooves on the E. face, and 1 groove on the W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T19N R37E <u>S 31 S 32</u></p> <p style="text-align: center;">1971</p> <p>bury the original corner stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
<hr/>	
	S. 89° 57' W., along the S. bdy. of sec. 31,
	Over rolling mountainous land, through medium sagebrush and native grass.
	Ascend 490 ft. over NE. slope, changing to E. slope.
25.00	Ridge, bears N. and S.; desc. 120 ft. over SW. slope.
30.00	Draw, drains SSE.; asc. 80 ft. over E. slope.
35.40	Ridge, bears N. and SSW.; desc. 70 ft. over NW. slope; enter scattered juniper and pinon.
40.09	<p>The ¼ sec. cor. of sec. 31 only, monumented with a basalt stone, 16x8x6 ins., firmly set in the ground, mkd. ¼ on the N. face, with a mound of stone N.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T19N R37E <u>¼ S 31</u></p> <p style="text-align: center;">1971</p> <p>bury the original corner stone alongside the iron post.</p>
	<hr/>
	N. 89° 48' W., beginning new measurement.
	Descend 180 ft. over NW. slope.