## DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 19 N., R. 37 E.

	1. 19 N., R. 5/ E.
CHAINS	
23.20	Spur, projects SE.; asc. 150 ft. over broken S. slope.
43.04	Point for the ½ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T19N R37E
٠	½ S 7 S 18
	1971
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor
·	Ascend 330 ft. along broken S. slope, through medium to dense juniper and pinon.
83.52	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 3 ins. diam., firmly set in the ground, extending 18 ins. above the ground, with brass cap mkd.
	T19 <b>N</b> R36E <b>R</b> 37E S 12 S 7 S 13 S 18
	1915
	From which the bearing trees marked in 1915:
	A juniper, 12 ins. diam., bears N. $71\frac{1}{2}^{\circ}$ E., 37 lks. dist., mkd. T19N R37E S7 BT.
	A pinon, 12 ins. diam., bears S. 85° E., 9 lks. dist., mkd. T19N R37E S18 BT.
·	A pinon, 14 ins. diam., bears S. 9 3/4° W., 53 lks. dist., mkd. T19N R36E S13 BT.
	A pinon, 10 ins. diam., bears N. 11° W., 18 lks. dist., mkd. T19N R36E S12 BT.
	This corner is set in the bottom of a narrow ravine, drains SE.
	raise a mound of stone, 4 ft. base, 1½ ft. high, around the iron post.
	From the cor. of secs. 7, 8, 17 and 18.
-	N. 1° 56' W., bet. secs. 7 and 8.