DEPENDENT RESURVEY OF THE EAST BOUNDARY OF T. 20 N., R. 38 E.

CHAINS	
	T 20N
	R38E R39E
	S 12 S 7
	1971
	bury the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	N. 1° 18' E., beginning new measurement.
/0.1/	
40.14	The cor. of secs. 1, 6, 7 and 12, monumented with a granite stone, 18x6x6 ins., mkd. with 1 notch on the N. edge and 5 nothces on the S. edge, firmly set in the ground.
	At the corner point
1	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20N R38E R39E S 1 S 6 S 12 S 7
	1971
	bury the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	N. 1° 39' E., bet. secs. 1 and 6.
	Over nearly level land, through greasewood and shadscale.
37.93	Point for the ½ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 20N
	R38E_R39E
	s 1 s 6
	1971
	raise a mound of stone, 6 ft. base, 4 ft. high, W. of cor.
	This corner is located on the edge of a dry lake bed, edge bears NE. and SW.