

DEPENDENT RESURVEY OF THE WEST BOUNDARY OF  
T. 20 N., R. 38 E.

CHAINS	
32.00	Ridge, bears ENE. and WSW.; desc. 50 ft. over NNW. slope.
40.02	Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T20N R37E R38E S 1   S 6 S 12   S 7</p>
	1971
	set a steel fence post, 6 ft. long, alongside the iron post and raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	This cor. is located at bottom of descent.
	N. 0° 29' E., bet. secs. 1 and 6.
	Over mountainous terrain, through scattering pine timber, shadscale and budsage; asc. 20 ft. along E. slope.
14.20	Wash, 50 lks. wide, 4 ft. deep, drains ESE.; asc. slightly along E. slope.
16.30	Wash, 40 lks. wide, 10 ft. deep, drains ESE.; asc. slightly along E. slope.
16.80	Trail road, bears E. and W.; asc. 50 ft. over SE. slope.
24.60	Spur, slopes E.; desc. 60 ft. over NE. slope.
31.00	Trail road, bears SE. and NW.; desc. slightly over NE. slope.
31.30	Byers Canyon with wash in bottom, 50 lks. wide, 2 ft. deep, drains ESE.; asc. 30 ft. over SSE. slope.
40.02	Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T20N R37E R38E ¼ S 1   S 6</p>
	1971
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.