

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF
T. 20 N., R. 38 E.

CHAINS	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.
39.59	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T20N R38E} \\ \frac{1}{4} \\ \text{S } 2 \frac{1}{2} \text{ S } 1 \end{array}$
	1971
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
82.87	Point for the closing cor. of secs. 1 and 2, at proportionate distance and on the Fourth Standard Parallel North; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \text{T21N R38E} \\ \text{S } 36 \\ \hline \text{S } 2 \frac{1}{2} \text{ S } 1 \\ \text{CC} \end{array}$
	T20N R38E
	1971
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this corner the standard cor. of secs. 35 and 36, T. 21 N., R. 38 E., bears S. $89^{\circ} 54' W.$, 11.96 chs. dist.
	Point for the N. $\frac{1}{4}$ sec. cor. of sec. 1, on the Fourth Standard Parallel North and at midpoint on the N. bdy. of sec. 1.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} \frac{1}{4} \text{ S } 1 \\ \hline \text{T20N R38E} \end{array}$
	1971
	raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.
	From this corner the standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 21 N., R. 38 E., bears S. $89^{\circ} 54' W.$, 11.795 chs. dist.