

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF
T. 20 N., R. 38 E.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T20N R38E

$\frac{1}{4}$
S 4 | S 3

1971

reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high. W. of cor.

N. $1^{\circ} 04'$ E., beginning new measurement.

28.10 Fence, bears SE. and NW.

39.84 Point for the closing cor. of secs. 3 and 4, at proportionate distance and on the Fourth Standard Parallel North; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N R38E

S 34
S 4 | S 3

C C

T20N R38E

1971

raise a mound of stone, 3 ft. base; 2 ft. high, S. of cor.

From this corner the standard cor. of secs. 33 and 34, T. 21 N., R. 38 E., bears N. $89^{\circ} 39'$ W., 12.48 chs. dist.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 3, on the Fourth Standard Parallel North and at midpoint on the N. bdy. of sec. 3.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 3

T20N R38E

1971

raise a mound of stone, 5 ft. base, 4 ft. high, S. of cor.

From this corner the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 21 N., R. 38 E., bears S. $89^{\circ} 54'$ W., 12.44 chs. dist.