

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF
T. 20 N., R. 38 E.

CHAINS		
	T20N R38E $\frac{1}{4}$ $\frac{S \ 4}{S \ 9}$	
	1971	
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.	
41.90	Fence, bears N. $14 \frac{3}{4}^{\circ}$ E. and S. $14 \frac{3}{4}^{\circ}$ W.	
63.00	Fence, bears S. $2 \frac{1}{4}^{\circ}$ E. and N. $2 \frac{1}{4}^{\circ}$ W.	
67.70	Trail road, bears NNE. and SSW.	
73.30	Trail road, bears SE. and NW.	
81.18	The cor. of secs. 4, 5, 8 and 9.	
	N. $0^{\circ} 33'$ E., bet. secs. 4 and 5.	
	Over nearly level land, through greasewood.	
12.50	Wash, 30 lks. wide, 3 ft. deep, drains NE.	
18.50	Trail road, bears S. $8 \frac{1}{4}^{\circ}$ E. and N. $8 \frac{1}{4}^{\circ}$ W.	
40.39	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, $2 \frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	T20N R38E $\frac{1}{4}$ S 5 S 4	
	1971	
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.	
47.00	Wash, 30 lks. wide, 2 ft. deep, drains ENE.	
71.50	Wash, 20 lks. wide, 2 ft. deep, drains SE.	
73.00	Graded road, bears NE. and SW.	
85.78	The closing cor. of secs. 4 and 5, at intersection with the Fourth Standard Parallel North, monumented with an unmarked wooden post, 2x2x20 ins., loosely set in a mound of earth. This is accepted as the best available evidence of the position of the original corner.	
	At the corner point	