

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF
T. 20 N., R. 38 E.

CHAINS

59.70

Wash, 10 lks. wide, 1 ft. deep, drains E.

84.34

Point for the closing cor. of secs. 5 and 6, at proportionate distance and on the Fourth Standard Parallel North; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21N R38E

S 32

S 6 | S 5

C C

T20N R38E

1971

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner the standard cor. of secs. 31 and 32, T. 21 N., R. 38 E., bears N. $89^{\circ} 51' W.$, 12.26 chs. dist.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 5, on the Fourth Standard Parallel North and at midpoint on the N. bdy. of sec. 5.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$ S 5

T20N R38E

1971

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 21 N., R. 38 E., bears N. $89^{\circ} 52' W.$, 11.945 chs. dist.

40.28

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 6, on the Fourth Standard Parallel North and at proportionate distance on the N. bdy. of sec. 6.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

 $\frac{1}{4}$ S 6

T20N R38E

1971

From this corner the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 21 N., R. 38 E., bears S. $89^{\circ} 50' W.$, 12.31 chs. dist.