

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,
T. 21 N., R. 39 E., (FOURTH STANDARD PARALLEL N.)

CHAINS	
39.00	<p>S. 89° 54' W., beginning new measurement.</p> <p>Leave sand dunes; enter dry lake bottom; bears NE. and SW.</p> <p>Point for the standard corner of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T21N R39E <u>S 31 S 32</u></p> <p style="text-align: center;">1970</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
40.35	<p>S. 89° 54' W., along the S. bdy. of sec. 31.</p> <p>Over nearly level dry lake bottom.</p> <p>Point for the standard ¼ sec. cor. of sec. 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T21N R39E <u>¼ S 31</u></p> <p style="text-align: center;">1970</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
80.70	<p>Point for the standard corner of Tps. 21 N., Rs. 38 and 39 E., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T21N R38E R39E <u>S 36 S 31</u></p> <p style="text-align: center;">1970</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>From this cor., the standard ¼ sec. cor. of sec. 34, T. 21 N., R. 38 E., bears S. 89° 54' W., 201.75 chs. dist., monumented with a 2½ in. iron post, set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 20 N., R. 38 E.</p>