

478

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
T. 1 S., R. 69 E.

CHAINS	
40.00	<p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented with a basalt stone, 20x16x8 ins., firmly set in the ground, mkd. $\frac{1}{4}$ on the N. face, with a mound of stone N.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R69E S 19 $\frac{1}{4}$ ——— S 30</p> <p style="text-align: center;">1971</p> <p>deposit the original corner stone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p style="text-align: center;">—————</p> <p>N. 89° 52' W., beginning new measurement.</p>
7.00	Wash, 30 lks. wide, 5 ft. deep, drains N.
8.60	Improved gravel road, bears N. and S.; asc. 200 ft. over E. slope.
29.30	Spur, slopes NE.; desc. 20 ft. over NW. slope.
31.82	<p>Intersect the E. bdy. of sec. 25, T. 1 S., R. 68 E.</p> <p>Point for the closing corner of secs. 19 and 30, T. 1 S., R. 69 E.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 6 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T1S T1S R68E R69E S 25 $\frac{S 19}{S 30}$ CC</p> <p style="text-align: center;">1971</p>
	<p>From this cor., the cor. of secs. 19, 24, 25 and 30, set in the 1902 survey, as described in the field notes of the concurrent resurvey of T. 1 S., R. 68 E., bears N. 89° 52' W., 3.96 chs. dist.</p>
	<p>From this same cor., the cor. of secs. 24 and 25, on the E. bdy. of T. 1 S., R. 68 E., monumented with an iron post, 2$\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 1 S., R. 68 E., bears N. 0° 06' E., 1.92 chs. dist.</p>
	<p>Land, rolling. Soil, sandy clay loam, to rocky. Undergrowth, sagebrush. Timber, none.</p>