

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 69 EAST

CHAINS

DEPENDENT RESURVEY OF THE FIFTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 69 EAST

Reestablishment of the Survey executed by  
Preble and Thorburn, U. S. Deputy Surveyors,  
in 1881,  
and dependently resurveyed by  
Emil Voigt, Cadastral Engineer,  
and Wilson McConkie, Public Land Surveyor,  
in 1940.

The description of the standard corner monuments found  
on this line are described herein and will now serve as  
Angle Points.

New standard corners are established at intervals of  
40 chs. from the standard corner of Tps. 26 N., Rs. 68  
and 69 E.

Beginning at the standard corner of Tps. 26 N.,  
Rs. 68 and 69 E., monumented with an iron post, 3 ins.  
diam., firmly set and mkd. as described in the official  
record, from which the original bearing tree

A juniper, 5 ins. diam., bears N. 3/4° W.,  
113 lks. dist., mkd. T26N R68E S36 SC BT.

N. 89° 53' E., along the S. bdy. of sec. 31.

Over rolling land, through scattered timber and under-  
growth.

- 0.70 Wash, 20 lks. wide, 2 ft. deep, drains WNW.
- 6.70 Wash, 20 lks. wide, 2 ft. deep, drains WSW.
- 8.80 Wash, 20 lks. wide, 2 ft. deep, drains WNW.; asc.  
140 ft. over NW. slope.
- 40.00 Point for the standard 1/4 sec. cor. of sec. 31.  
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

S C  
T26N R69E  
1/4 S 31

1971

raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.