

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF
T. 27 N., R. 69 E.

CHAINS	
12.00	Ridge, bears N. and S.
24.50	Spur, slopes S.
28.30	Ravine, drains S.
36.00	Ridge, bears N. and S.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd. <div style="text-align: center;"> T27N R69E $\frac{1}{4}$ $\frac{S\ 29}{S\ 32}$ 1971 </div>
74.50	Spur, slopes S.
79.96	The cor. of secs. 29, 30, 31 and 32. Land, rolling. Soil, sandy clay and gravel. Timber, juniper. Undergrowth, sagebrush and greasewood.
	S. $89^{\circ} 54'$ W., bet. secs. 30 and 31. Over rolling land, through scattered undergrowth.
38.70	Trail road, bears N. and S.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T27N R69E $\frac{1}{4}$ $\frac{S\ 30}{S\ 31}$ 1971 </div>
	raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
64.50	Trail road, bears N. and S.
79.16	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the independent resurvey of the W. bdy. of T. 27 N., R. 69 E., executed under Group No. 463, in 1969.