

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF  
T. 28 N., R. 69 E.

CHAINS	
74.10	Wash, 20 lks. wide, 2 ft. deep, drains SSW.
76.80	Wash, 10 lks. wide, 2 ft. deep, drains S.
78.44	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the independent resurvey of the west boundary of T. 28 N., R. 69 E., executed under Group No. 463, in 1969.</p> <p>Land, rolling. Soil, sandy clay and gravel. Timber, juniper and pinon. Undergrowth, greasewood and bunchgrass.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0° 01' W., bet. secs. 19 and 20.</p> <p>Over rolling land, through scattered timber and undergrowth; asc. 260 ft. over S. slope.</p>
30.50	Ridge, bears E. and W.; desc. 270 ft. over broken N. slope.
40.00	<p>Point for the ¼ sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone to cap, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R69E</p> <p>¼</p> <p>S 19   S 20</p> <p>1971</p> </div>
44.50	Wash, 20 lks. wide, 1 ft. deep, drains ENE.
47.70	Wash, 20 lks. wide, 1 ft. deep, drains ESE.
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R69E</p> <p>S 18   S 17</p> <p>S 19   S 20</p> <p>1971</p> </div> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy clay and gravel. Timber, juniper and pinon. Undergrowth, greasewood and bunchgrass.</p>