

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES OF
T. 28 N., R. 69 E.

CHAINS		
76.50	Spur, slopes S.; desc. 50 ft. over W. slope.	
78.34	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the independent resurvey of the west boundary of T. 28 N., R. 69 E., executed under Group No. 463, in 1969.</p> <p>Land, rolling. Soil, sandy clay and gravel. Timber, juniper and pinon. Undergrowth, sagebrush, greasewood and bunchgrass.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0° 01' W., bet. secs. 17 and 18.</p> <p>Over rolling land, through scattered timber and undergrowth.</p>	
0.10	Bladed road, bears NNW. and SSE.	
26.10	Bladed road, bears NE. and SW.	
40.00	<p>Point for the ¼ sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28N R69E ½ S 18 S 17 1971</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 60 3/4° E., 15 lks. dist., mkd. ¼ S17 BT.</p> <p style="padding-left: 40px;">A pinon, 12 ins. diam., bears S. 50¼° W., 158 lks. dist., mkd. ¼ S18 BT.</p> <p style="padding-left: 40px;">Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Asc. 40 ft. over rolling S. slope.</p>	
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	