INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 28 N., R. 70 E.

	T. 28 N., R. 70 E.
CHAINS	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T28N R70E
	大 S 4 S 3
	1971
70 (7	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
78.67	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the independent resurvey of the south boundary of T. 29 N., R. 70 E., surveyed under Group No. 463, Nevada, in 1970.
	Land, nearly level. Soil, sandy clay and gravel. Undergrowth, sagebrush, greasewood and Indian ricegrass. Timber, none.
	From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the independent resurvey of the north boundary of T. 27 N., R. 70 E., surveyed concurrently under this same group.
	N. 0° 06' E., bet. secs. 34 and 35.
	Over rolling land, through scattered timber and under- growth; asc. 120 ft. along W. slope to the 社 sec. cor.
2.10	Wash, 15 1ks. wide, 3 ft. deep, drains SSE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T28N R70E
	s 34 s 35
	1971
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	Asc. 130 ft. over SW. slope.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.