

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 28 N., R. 70 E.

CHAINS

EAST, bet. secs. 26 and 35.

Over rolling land, through scattered undergrowth; asc.
130 ft. over W. slope.

17.42 Intersect the Nevada-Utah State Line.

Point for the closing cor. of secs. 26 and 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T28N
R70E
CC $\frac{S\ 26}{S\ 35}$

1971

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
from this corner

Mile Post No. 74 on the Nevada-Utah State Line,
bears S. $0^{\circ} 03'$ E., 23.70 chs. dist.

Land, rolling.
Soil, sandy clay and gravel.
Undergrowth, sagebrush and greasewood.
Timber, none.

The point for the E. $\frac{1}{4}$ sec. cor. of sec. 35 on the
Nevada-Utah State Line and at midpoint on the E. bdy. of
sec. 35.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T28N
R70E
 $\frac{1}{4}$
S 35

1971

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
and set a steel fence post, 5 ft. long, 24 ins. in the
ground, alongside the iron post.

from this corner

Mile Post No. 74 on the Nevada-Utah State Line,
bears N. $0^{\circ} 07'$ W., 16.29 chs. dist.