

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 28 N., R. 70 E.

CHAINS	
26.50	Ridge, bears N. and S.; desc. 190 ft. over E. slope.
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock and in a mound of stone to cap, 6 ft. base, with brass cap mkd.
	<div style="text-align: center;"> T28N R70E $\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$ </div>
	1971
	Desc. 40 ft. over E. slope.
47.00	Draw, drains NE.
61.30	Wash, 10 lks. wide, 4 ft. deep, drains N.
71.50	Wash, 15 lks. wide, 2 ft. deep, drains NNW.; asc. 50 ft. over rolling W. slope.
79.98	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling. Soil, sandy clay and gravel. Undergrowth, sagebrush and greasewood. Timber, none.
	EAST, bet. secs. 23 and 26.
	Over rolling land, through scattered undergrowth; asc. 30 ft. over rolling W. slope to the cor.
2.80	Wash, 20 lks. wide, 3 ft. deep, drains NW.
17.39	Intersect the Nevada-Utah State Line.
	Point for the closing cor. of secs. 23 and 26.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T28N R70E CC $\frac{S\ 23}{S\ 26}$ </div>
	1971
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. and set a steel fence post, 5 ft. long, 24 ins. in the ground, alongside the iron post.