

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 34 N., R. 39 E.

<p>CHAINS 40.24</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, monumented with a basalt stone, 18x12x4 ins., mkd. $\frac{1}{4}$ on the W. face and firmly set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T34N R39E R40E $\frac{1}{4}$ S 12 S 7</p> <p style="text-align: center;">1971</p> <p>bury the original corner stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' E., beginning new measurement.</p> <p>Desc. 350 ft. over a NW. slope.</p>
<p>25.50</p>	<p>Slope changes; desc. 90 ft. over a N. slope.</p>
<p>39.95</p>	<p>The cor. of secs. 1, 6, 7 and 12, monumented with an unmarked granite stone, 24x16x8 ins., firmly set in a mound of stone. This position is harmoniously related to existing original corners and is accepted as the best existing evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone to cap, 6 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T34N R39E R40E S 1 S 6 S 12 S 7</p> <p style="text-align: center;">1971</p> <p>bury the unmarked stone alongside the iron post.</p>
<p>8.70</p>	<p>N. 0° 26' W., bet. secs. 1 and 6.</p>
<p>8.80</p>	<p>Over nearly level land, through sagebrush and bunchgrass; desc. 100 ft. over a N. slope.</p> <p>Trail road, bears NNE. and SW.; desc. a N. slope.</p> <p>Fence corner, bears W., 6 lks. dist., from which fences bear SW. and N.; thence along fence.</p>