

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 34 N., R. 39 E.

CHAINS	
80.46	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of T. 35 N., R. 39 E., resurveyed concurrently under this same group.
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.
	N. 2° 13' W., bet. secs. 32 and 33.
	Over mountainous land, through sagebrush and bunchgrass; desc. 20 ft. over a N. slope.
0.60	Draw, drains W.; asc. 60 ft. over a S. slope.
5.20	Trail road, bears E. and W.
5.30	Fence, bears E. and W.; asc. 30 ft. over a S. slope.
6.80	Slope changes; asc. 80 ft. over a SW. slope.
16.50	Spur, slopes W.; desc. 10 ft. over a W. slope.
18.30	Slope changes; desc. 100 ft. over a NW. slope.
23.80	Draw, drains W.; asc. 90 ft. over a S. slope.
30.20	Spur, slopes SW.; desc. 180 ft. over a NW. slope.
35.30	Draw, drains W.; asc. 30 ft. over a S. slope.
39.38	Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to the cap, 3 ft. base, with brass cap mkd.
	T34N R39E
	S 32 S 33
	1971
	Corner is located on a spur, sloping SW.
	Desc. 90 ft. over a NW. slope.
46.70	Clear Creek, 10 lks. wide, 4 ft. deep, 6 ins. water, course SW.; asc. 150 ft. over a SW. slope.
55.50	Top of ascent; desc. 10 ft. over a NE. slope.
58.40	Draw, drains SE.; asc. 200 ft. over a SW. slope.