

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 34 N., R. 39 E.

CHAINS	
23.70	Draw, drains NE.; desc. 40 ft. over a NE. slope.
28.40	Spur, slopes NE.; desc. 120 ft. over a NE. slope.
34.70	Spur, slopes NE.; desc. 60 ft. over a NE. slope.
36.50	Draw, drains NE.; desc. 40 ft. over a NE. slope.
40.33	Point for the $\frac{1}{2}$ sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T34N R39E
	$\frac{1}{2}$ S 6 S 5
	1971
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
42.40	Spur, slopes NE., desc. 130 ft. over a NE. slope.
48.70	Draw, drains NE.; desc. 50 ft. over a NE. slope.
52.50	Spur, slopes E.; desc. 330 ft. over a NE. slope.
62.60	Sonoma Creek, 30 lks. wide, 2 ft. deep, course NW.; asc. 70 ft. over a SW. slope.
78.20	Spur, slopes NW.; desc. 100 ft. over a N. slope.
80.82	The closing cor. of secs. 5 and 6, on the S. bdy. of T. 35 N., R. 39 E., monumented with a granite stone, 18x8x6 ins., mkd. with 5 notches on the E. edge and 1 notch on the W. edge and firmly set in the ground.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T35N R39E
	S 31 <hr style="width: 50%; margin: auto;"/> S 6 S 5
	C C
	T34N R39E
	1971
	bury the original corner alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of the cor.