

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 39 E.

CHAINS	
25.30	Draw, drains ESE.; asc. 50 ft. over SE. slope.
33.40	Spur, slopes NE.; desc. 30 ft. over N. slope.
35.80	Draw, drains ENE., changing to NE.; asc. 30 ft. over S. slope.
39.75	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T35N R39E $\frac{1}{4}$ S 3 S 2 1971</p>
	raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
40.00	Spur, slopes ENE.; desc. 30 ft. over ENE. slope.
45.00	Draw, drains SE.; asc. 220 ft. over steep S. slope.
54.40	Spur, slopes SE.; asc. 90 ft. along E. slope.
81.04	Intersect the Seventh Standard Parallel North.
	Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. This corner falls on E. face of rock outcrop, where it is impracticable to set a monument.
	Point selected for the witness closing corner of secs. 2 and 3, on the Seventh Standard Parallel North, bears N. $89^{\circ} 55'$ E., 0.07 chs. dist.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">W C T36N R39E S 34 ← S 3 S 2 C C T35N R39E 1971</p>
	set a steel fence post, $5\frac{1}{2}$ ft. long, $2\frac{1}{2}$ ft. in the ground, alongside the iron post.
	From the true point, the standard cor. of secs. 34 and 35, T. 36 N., R. 39 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record, bears N. $89^{\circ} 55'$ E., 13.78 chs. dist.