

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 39 E.

CHAINS	
	N. 0° 45' W., bet. secs. 3 and 4.
	Over mountainous land, through medium undergrowth.
3.80	Spur, slopes SE.; desc. 40 ft. along E. slope.
14.00	Draw, drains NE.; asc. 450 ft. along steep E. slope.
39.70	Spur, slopes SE.; desc. 30 ft. along E. slope.
40.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T35N R39E $\frac{1}{4}$ S 4 S 3</p>
	1971
	Descend 20 ft. along steep E. slope.
44.80	Rocky spur, slopes NE.; desc. 900 ft. over NW. slope, changing to W. slope.
81.80	Intersect the Seventh Standard Parallel North.
	Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T36N R39E S 33 S 4 S 3 C C T35N R39E</p>
	1971
	raise a mound of stone, 5 ft. base, 4 ft. high, S. of cor.
	From this corner, the standard cor. of secs. 33 and 34, T. 36 N., R. 39 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record, bears S. 89° 57' E., 13.82 chs. dist.
	From this same corner, the standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 36 N., R. 39 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record, bears N. 89° 57' W., 26.23 chs. dist.