

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 39 E.

CHAINS	
58.50	Fence, bears E. and W.; asc. 50 ft. over SSW. slope.
61.60	Spur, slopes SW.; desc. 120 ft. along W. slope.
82.09	Intersect the Seventh Standard Parallel North.
	<p>The closing cor. of secs. 4 and 5, monumented with a granite stone, 16x10x8 ins., plainly mkd. CC on the S. face and 2 grooves on the W. face and 4 grooves on the E. face, firmly set in the ground, with a mound of stone S.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R39E $\frac{S}{S} \frac{32}{5 S} \frac{4}{C} \frac{C}{T35N R39E}$</p>
	<p style="text-align: center;">1971</p>
	<p>bury the corner stone alongside the iron post and raise a mound of stone, 5 ft. base, 4 ft. high, S. of cor.</p>
	<p>From this corner, the standard cor. of secs. 32 and 33, T. 36 N., R. 39 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record, bears S. 89° 59' E., 12.82 chs. dist.</p>
	<p>From this same corner, the standard ¼ sec. cor. of sec. 32, T. 36 N., R. 39 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record, bears N. 89° 59' W., 26.01 chs. dist.</p>
	<p>The point for the ¼ sec. cor. on the N. bdy. of sec. 4 is on the S. bdy. of T. 36 N., R. 39 E. and at midpoint on the N. bdy. of sec. 4.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock and in a collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R39E $\frac{¼}{¼} \frac{S}{S} \frac{4}{T35N R39E}$</p>
	<p style="text-align: center;">1971</p>
	<p>raise a mound of stone, 3½ ft. base, 2½ ft. high, S. of cor.</p>