

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 39 E.

CHAINS	
78.00	Fence, bears NW. and SE.
82.65	Intersect the Seventh Standard Parallel North.
	<p>The closing cor. of secs. 5 and 6, monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record.</p>
	<p>From this corner, the standard cor. of secs. 31 and 32, T. 36 N., R. 39 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record, bears N. 89° 46' E., 12.90 chs. dist.</p>
	<p>From this same corner, the standard ¼ sec. cor. of sec. 31, T. 36 N., R. 39 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record, bears S. 89° 46' W., 27.25 chs. dist.</p>
	<p>The point for the ¼ sec. cor. on the N. bdy. of sec. 5 is on the S. bdy. of T. 36 N., R. 39 E. and at midpoint on the N. bdy. of sec. 5.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p>T36N R39E</p>
	<p>¼ S 5 T35N R39E</p>
	<p>1971</p>
	<p>set a steel fence post, 5½ ft. long, 2½ ft. in the ground, alongside the iron post and raise a mound of stone, 3½ ft. base, 2½ ft. high, S. of cor.</p>
	<p>From this corner, the standard ¼ sec. cor. of sec. 32, T. 36 N., R. 39 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record, bears N. 89° 44' E., 13.48 chs. dist.</p>
	<p>From this same corner, the standard cor. of secs. 31 and 32, T. 36 N., R. 39 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record, bears S. 89° 44' W., 26.59 chs. dist.</p>
	<p>The point for the ¼ sec. cor. on the N. bdy. of sec. 6 is on the S. bdy. of T. 36 N., R. 39 E. and at proportionate distance on the N. bdy. of sec. 6.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 5 ft. base to top, with brass cap mkd.</p>