

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 38 N., R. 44 E.

CHAINS	
	N. 0° 06' W., bet. secs. 1 and 6.
	Over mountainous land, through native grasses; asc. 240 ft. over SE. slope.
16.00	Begin steep ascent; asc. 800 ft. over SSW. slope.
35.00	Top of bluff, 30 ft. high, bears ESE. and WNW.; desc. 30 ft. over NE. slope.
40.71	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 5 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T38N R44E R45E $\frac{1}{4}$ S 1 S 6 1971</p>
	Enter scattered mountain mahogany; desc. 190 ft. over NE. slope.
54.10	Ravine, drains WNW.; asc. 160 ft. over SSW. slope.
62.70	Top of bluff, 30 ft. high, bears ENE. and WSW.; asc. 30 ft. over plateau.
73.00	Top of plateau, bears ENE. and WSW.; desc. 120 ft. over NNW. slope.
81.42	The cor. of Tps. 38 and 39 N., Rs. 44 and 45 E., monumented with a limestone, 20x12x12 ins., dimly mkd. with 6 notches on the N., E., S. and W. edges, and firmly set in a small mound of stone.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 6 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T39N R44E R45E S 36 S 31 S 1 S 6 T38N 1971</p>
	deposit the original corner stone alongside the iron post.