DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 38 N., R. 44 E.

 	T. 38 N., R. 44 E.
CHAINS	From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the 1970 resurvey of T. 38 N., R. 45 E.
	S. 89° 48' W., bet. secs. 13 and 24.
•	Asc. over gentle SE. slope, through sagebrush.
0.30	Telephone line, bears N. 60½° E. and S. 60½° W.
2.30	Fence, bears S. 16° E. and N. 16° W.
8.90	Trail road, bears ENE. and WSW.
40.00	Creek, 2 lks. wide, 1 ft. deep, course SE.
40.85	Point for the ½ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
,	T38N R44E S 13 S 24
	1971
	set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.
43.90	Water line, bears S. 6½° E. and N. 6½° W.
49.30	Fence, bears S. 16° E. and N. 16° W.
50.80	Trail road, parallels fence.
75.00	Trail road, bears SSE. and NNW.
81.70	The cor. of secs. 13., 14, 23 and 24.
	N. 0° 43' W., bet. secs. 13 and 14.
	Over rolling hills, through sagebrush; asc. 160 ft. over S. slope.
42.00	Trail road, bears NW. and SE.
42.36	Point for the ½ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.