

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,  
T. 38 N., R. 44 E.

## CHAINS

The cor. of Tps. 37½ and 38 N., R. 43 E., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record. I remark the brass cap as follows:

T38N  
R43E R44E  
S 36 | S 31  
S 36 |  
T37½N

1963

From the cor. of secs. 29, 30, 31 and 32.

N. 0° 42' E., bet. secs. 29 and 30.

Over nearly level land, through sagebrush.

10.50 Telephone line, bears S. 35° E. and N. 35° W.

14.80 Graded road, parallels telephone line.

25.00 Creek, 20 lks. wide, 6 ft. deep, course SE.

39.96 The ¼ sec. cor. of secs. 29 and 30, monumented with an unmarked squared wooden post, 2x2x20 ins., loosely set in a mound of earth and evidence of pits.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T38N R44E  
¼  
S 30 | S 29

1971

reset the wooden post alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

N. 0° 38' E., beginning new measurement.

Asc. 90 ft. over a gentle S. slope.

39.70 Wash, 10 lks. wide, 1 ft. deep, drains SE.

39.87 The cor. of secs. 19, 20, 29 and 30, monumented with an unmarked squared wooden post, 2x2x20 ins., loosely set in a mound of stone and evidence of pits.

At the corner point