

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY OF
T. 36 N., R. 46 E.

CHAINS	Desc. 10 ft. over NE. slope.
42.10	Ravine, drains SE.; asc. 490 ft. over SW. slope.
57.70	Spur, slopes SE.; desc. 160 ft. over NE. slope.
80.08	<p>The cor. of secs. 1, 6, 7 and 12, monumented with a granite stone, 20x14x6 ins., plainly mkd. with 5 notches on the S. face and 1 notch on the N. face and firmly set in a circle of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on bedrock over a cross (X) and in a mound of stone to cap, 5 ft. base, with brass cap mkd.</p> <div>T36N R45E R46E S 1 S 6 S 12 S 7</div> <p>1971</p> <p>bury the corner stone alongside the iron post.</p> <p>from which</p> <p>A spring, draining S., bears N. 77 3/4° E., 11.62 chs. dist.</p> <hr/> <p>N. 0° 17' E., bet. secs. 1 and 6.</p> <p>Over mountainous land, through scattered sagebrush and bunchgrass; desc. 30 ft. over NE. slope.</p> <p>1.30 Sixmile Creek, drains SE.; asc. 980 ft. over broken ledgy S. slope.</p> <p>27.00 Ridge, bears E. and W.; desc. 280 ft. over NE. slope.</p> <p>39.51 The ¼ sec. cor. of secs. 1 and 6, monumented with a granite stone, 14x10x6 ins., dimly mkd. ¼ and firmly set in a circle of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.</p> <div>T36N R45E R46E ¼ S 1 S 6</div> <p>1971</p> <p>bury the corner stone alongside the iron post.</p> <hr/>