

DEPENDENT RESURVEY OF THE NORTH BOUNDARY OF  
T. 36 N., R. 46 E.

CHAINS	
	T37N R46E S 31 $\frac{1}{4}$ ——— S 6 T36N  1971
	Desc. 220 ft. along S. slope.
50.50	Ravine, drains ESE.; asc. 300 ft. over NE. slope.
54.60	Spur ESE.; along S. slope.
72.30	Steep ledgy spur, slopes S.; desc. 40 ft. over SW. slope.
80.67	The cor. of Tps. 36 and 37 N., Rs. 45 and 46 E.
<hr/> RETRACEMENT OF A PORTION OF THE SEVENTH STANDARD PARALLEL NORTH, THROUGH RANGE 46 EAST, MOUNT DIABLO MERIDIAN, NEVADA. <hr/>	
Retracement of a Portion of the Resurvey Executed by W. A. Pray, U. S. Surveyor, and J. G. Collins, U. S. Transitman, in 1913 and 1914. <hr/>	
	From the standard cor. of Tps. 36 N., Rs. 46 and 47 E., monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.
	S. 89° 37' W., along the S. bdy. of sec. 36.
	Over gently rolling land, through medium sagebrush.
34.48	The closing cor. of Tps. 35 N., Rs. 46 and 47 E., monu- mented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record, bears NORTH, 0.06 chs. dist.
40.34	The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.
	<hr/> S. 89° 32' W., beginning new measurement. <hr/>
	Over rolling land.
5.40	Trail road, bears NE. and SW.
30.60	Improved gravel road, bears NE. and SW.
40.36	The standard cor. of secs. 35 and 36, monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.