

RETRACEMENT OF A PORTION OF THE SEVENTH STANDARD PARALLEL NORTH
THROUGH RANGE 46 E.

CHAINS	
	<p>S. 89° 38' W., along the S. bdy. of sec. 35.</p> <p>Over rolling land, through medium sagebrush.</p>
40.31	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record.</p> <hr/>
	<p>S. 89° 33' W., beginning new measurement.</p> <p>Over rolling land.</p>
34.80	<p>Trail road, bears NE. and SW.</p>
40.31	<p>The standard sec. cor. of secs. 34 and 35, monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record.</p> <hr/>
<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 36 N., R. 46 E., MOUNT DIABLO MERIDIAN, NEVADA.</p> <hr/>	
<p>Reestablishment of the Survey Executed by Hatch, Eaton and Smyles, U. S. Deputy Surveyors, in 1872; and a portion of the Dependent Resurvey Executed by W. A. Pray, U. S. Deputy Surveyor, and J. G. Collins, U. S. Transitman, in 1913 and 1914.</p> <hr/>	
<p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp.</p>	
<p>N. 0° 02' W., bet. secs. 35 and 36.</p>	
<p>Over gently rolling land, through medium sagebrush.</p>	
39.20	<p>Trail road, bears ENE. and WSW.</p>
40.14	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>
<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
<p style="text-align: center;">T36N R46E $\frac{1}{4}$ S 35 S 36</p>	
<p style="text-align: center;">1971</p>	
<p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
<p>Over gently rolling land.</p>	