

DEPENDENT RESURVEY OF A PORTION OF THE NINTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 55 EAST, MDM, NEVADA

CHAINS	
	N. 89° 59' W., beginning new measurement.
	Descend gradually over W. slope.
0.30	Draw, drains NNE.; asc. 100 ft. over E. slope.
8.00	Ridge, bears N. and S.; desc. 150 ft. over W. slope.
15.00	Draw, drains N.; asc. 400 ft. over E. slope.
36.60	Ridge, bears N. and S.; desc. 40 ft. over W. slope.
39.63	The standard cor. of secs. 35 and 36, monumented with a granite stone, 18x6x6 ins., mkd. with 5 grooves on the W. face, 1 groove on the E. face and SC on the N. face, firmly set in the ground, with a mound of stone N. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	S C
	T46N R55E
	S 35   S 36
	1971
	bury the original corner stone alongside the iron post, and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 46 N., R. 55 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of a Portion of the Survey Executed by U. S. Deputy Surveyor George A. Bellinger, in 1904
	From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp.
	N. 0° 07' W., bet. secs. 35 and 36.
	Over mountainous land, through medium sagebrush and native grass; desc. 210 ft. along W. slope, changing to NW. slope.
39.94	The ¼ sec. cor. of secs. 35 and 36, monumented with a granite stone, 12x8x8 ins., mkd. ¼ on the W. face, firmly set in the ground, with a scattered mound of stone W. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.