

DEPENDENT RESURVEY OF A PORTION OF THE NINTH STANDARD PARALLEL NORTH,
THROUGH RANGE 56 EAST, MDM, NEVADA

CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE NINTH STANDARD PARALLEL NORTH, THROUGH RANGE 56 EAST, MOUNT DIABLO MERIDIAN, NEVADA
	<p>Reestablishment of a Portion of the Survey Executed by U. S. Deputy Surveyor Dennis Scully, in 1896.</p> <hr/> <p>The standard cor. of secs. 35 and 36, monumented with a granite stone, 17x11x9 ins., mkd. with 5 grooves on the W. face, 1 groove on the E. face, and SC on the N. face, firmly set in the ground, with a scattered mound of stone N. of cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T46N R56E S C S 35 S 36</p> <p style="text-align: center;">1972</p> <p>bury the original corner stone alongside the iron post. N. 89° 59' W., along the S. bdy. of sec. 35.</p> <p>Over mountainous land, through scattered sagebrush and native grass; asc. 350 ft. over SE. slope.</p> <p>18.00 Ridge, bears NE. and SW.; desc. gradually.</p> <p>22.67 The closing cor. of secs. 1 and 2, T. 45 N., R. 56 E., monumented with a granite stone, 20x12x6 ins., badly deteriorated with no visible marks, firmly set in the ground, with a scattered mound of stone S. of cor.</p> <p>NOT REMONUMENTED</p> <p>rebuild the mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>Descend gradually.</p> <p>36.50 Draw, drains N.; asc. 50 ft. over E. slope.</p> <p>39.60 Spur, projects N.; desc. gradually over W. slope.</p> <p>40.40 The standard ¼ sec. cor. of sec. 35, monumented with a granite stone, 16x8x8 ins., mkd. ¼ on the N. face and firmly set in the ground.</p> <p>At the corner point</p>