

DEPENDENT RESURVEY OF A PORTION OF THE NINTH STANDARD PARALLEL NORTH,
THROUGH RANGE 56 EAST, MDM, NEVADA

CHAINS	
	S. 89° 56' W., along the S. bdy. of sec. 31.
	Over mountainous land, through medium sagebrush and native grass; asc. 110 ft. over broken SE. slope.
12.00	High spur, projects SW.; desc. 250 ft. over broken NW. slope, changing to W. slope.
13.60	Fence, bears NE. and SW., irregularly.
21.67	The closing cor. of secs. 5 and 6, T. 45 N., R. 56 E., monumented with an iron post, 2½ ins. diam., exposed 8 ins. above ground, with brass cap mkd.
	T46N R56E
	S 6 S 5
	C C
	T45N R56E
	1967
	I remark this to read
	T46N R56E
	S 31
	S 6 S 5
	C C
	T45N R56E
	1967
	1971
	Descend 340 ft. over W. slope.
40.01	The standard ¼ sec. cor. of sec. 31, monumented with a granite stone, 12x12x10 ins., mkd. ¼ SC on the N. face and firmly set in the ground.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	S C
	T46N R56E
	¼ S 31
	1971
	bury the original corner stone alongside the iron post.
	WEST, beginning new measurement.
	Descend 210 ft. over broken W. slope.
10.20	Meadow Creek, course N., irregularly.