

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 46 N., R. 56 E., MDM, NEVADA

CHAINS		
	T46N R56E $\frac{1}{4}$ S 1 S 2 1971	
	bury the original corner stone alongside the iron post.	
	<hr style="width: 20%; margin: auto;"/>	
	N. 0° 10' E., beginning new measurement.	
	Ascend 280 ft. over SW. slope.	
10.00	Spur, projects SE.; asc. 40 ft. along E. slope.	
14.00	Top of ascent; desc. 60 ft. along E. slope.	
17.00	Saddle on ridge, bears NE. and SW.; asc. 10 ft. along W. slope.	
23.00	Head of draw, drains W.; asc. 40 ft. over SW. slope.	
29.50	Top of ascent; desc. 40 ft. along W. slope.	
37.50	Spur, projects NNW.; desc. 40 ft. over NE. slope.	
40.50	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent dependent resurvey of a portion of the S. bdy. T. 47 N., R. 56 E., executed under this same group.	
	<hr style="width: 20%; margin: auto;"/>	
	From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp.	
	N. 0° 01' W., bet. secs. 34 and 35.	
	Over mountainous land, through medium sagebrush and native grass; asc. 600 ft. along E. slope.	
39.91	The ¼ sec. cor. of secs. 34 and 35, monumented with a granite stone, 32x16x8 ins., mkd. ¼ on the W. face, firmly set in the ground, with a scattered mound of stone W. of cor.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.	
	T46N R56E $\frac{1}{4}$ S 34 S 35 1972	
	bury the original corner stone alongside the iron post.	
	<hr style="width: 20%; margin: auto;"/>	