

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 46 N., R. 56 E., MDM, NEVADA

CHAINS	
26.00	Spring branch, course SSW., irregularly; asc. 130 ft. along broken E. slope.
27.00	Trail road, bears NNE. and SSW.
39.50	Draw, drains SE.; asc. gradually along E. slope.
39.96	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with a basalt stone, 12x11x8 ins., mkd. $\frac{1}{4}$ on the W. face, firmly set in the ground, with a mound of stone W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T46N R56E $\frac{1}{4}$ S 4 S 3</p> <p style="text-align: center;">1972</p> <p>bury the original corner stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 04' W., beginning new measurement.</p> <p>Ascend 250 ft. along broken E. slope.</p>
26.00	Spur, projects E.; desc. 80 ft. along E. slope.
39.87	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent dependent resurvey of a portion of the S. bdy., T. 47 N., R. 56 E., executed under this same group.
	<p>The cor. of secs. 16, 17, 20 and 21, monumented with an old mound of stone, partially embedded in the ground; no marked stone found. This position is harmoniously related to other existing corners in the survey, and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T46N R56E S 17 S 16 S 20 S 21</p> <p style="text-align: center;">1972</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>