

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 46 N., R. 56 E., MDM, NEVADA

CHAINS	
	Ascend gradually over S. slope.
20.00	Leave meadow, bears E. and W.
21.60	Graded road, bears E. and W.; asc. 370 ft. over broken S. slope to spur.
24.90	Telephone line, abandoned, bears E. and W.
32.50	Rocky spur, projects SW.; asc. 80 ft. over broken SS. slope.
39.35	The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent dependent resurvey of a portion of the S. bdy. of T. 47 N., R. 56 E., executed under this same group.
	From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp.
	N. 0° 04' W., bet. secs. 31 and 32.
	Over mountainous land, through medium sagebrush and native grass; asc. 340 ft. over broken SE. slope.
15.00	High spur, projects SW.; desc. gradually along W. slope.
16.40	Fence, bears NE. and SW.; desc. 300 ft. over W. slope, changing to N. slope.
37.90	Draw, drains NW.; asc. 50 ft. over SW. slope.
39.79	The ¼ sec. cor. of secs. 31 and 32, monumented with a granite stone, 14x6x2 ins., mkd. ¼ on the W. face, firmly set in the ground, with a scattered mound of stone W. of cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T46N R56E ¼ S 31   S 32</p> <p style="text-align: center;">1971</p>
	bury the original corner stone alongside the iron post.
	N. 0° 09' W., beginning new measurement.
	Ascend 100 ft. over SW. slope.
9.00	Spur, projects W.; desc. 200 ft. along broken W. slope.