

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 69 E., MDM, NEVADA

CHAINS		
	<p>from this corner</p> <p>The standard cor. of secs. 33 and 34, T. 31 N., R. 69 E., monumented with an iron post, 2 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, through R. 69 E., resurveyed concurrently under this same group, bears S. 88° 52' E., 12.31 chs. dist.</p>	
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the independent resurvey of the north bdy. of T. 29 N., R. 69 E., executed under Group No. 463, in 1969 and 1970.</p> <p>N. 0° 03' W., bet. secs. 32 and 33.</p> <p>Over mountainous land, through medium timber; asc. 300 ft. over S. slope.</p>	
40.00	<p>Point for the ¼ sec. cor. of secs. 32 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30N R69E ¼ S 32 S 33</p> <p style="text-align: center;">1971</p>	
	<p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Ascend 230 ft. over S. slope.</p>	
52.00	<p>Ridge, bears WNW. and SSE.; desc. 280 ft. over N. slope.</p>	
63.90	<p>Draw, drains W.; trail road in bottom of draw, bears E. and W.; asc. 140 ft. over S. slope.</p>	
80.00	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock over a cross (X) and in a mound of stone, 5 ft. base to cap, with brass cap mkd.</p> <p style="text-align: center;">T30N R69E S 29 S 28 S 32 S 33</p> <p style="text-align: center;">1971</p> <p>Land, mountainous. Soil, sandy clay and rocky. Timber, juniper and pinon. Undergrowth, sagebrush, greasewood and bunchgrass.</p>	