

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 69 E., MDM, NEVADA

CHAINS	
14.30	Trail road, bears SW. and NE., 3.00 chs., thence NNW.; asc. 20 ft. along E. slope.
28.50	Same road, bears NNW. and SSE.; asc. gradually.
29.10	Draw, drains ESE.; asc. 70 ft. over SW. slope.
39.00	Spur, slopes SSE.; asc. gradually along E. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T30N R69E $\frac{1}{4}$ S 6 S 5 1972
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Ascend 80 ft. along E. slope.
56.00	Head of draw, drains E.; asc. gradually along E. slope.
60.00	Spur, slopes SE.; desc. 100 ft. over NE. slope.
65.20	Ravine, drains SE.; asc. 100 ft. over SW. slope.
68.70	Spur, slopes SE.; thence along E. slope.
71.00	Head of draw, drains E.; asc. 30 ft. along E. slope.
74.00	Trail road, along top of ridge, bears NE. and SW.; desc. 40 ft. over NW. slope.
80.00	Point for the $80 \frac{1}{16}$ sec. cor. of secs. 5 and 6. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T30N R69E $\frac{1}{16}$ S 6 S 5 80 1972
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Descend 50 ft. over NW. slope.
86.69	Intersect the Sixth Standard Parallel North. Point for the closing cor. of secs. 5 and 6. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.