INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 69 E., MDM, NEVADA

CHAINS

¼ S 6
T30N R69E

1971

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

from this corner

The standard cor. of Tps. 31 N., Rs. 68 and 69 E., monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the field notes of the dependent resurvey of a portion of the Sixth Standard Parallel North, through R. 68 E., resurveyed under this same group, bears S. 88° 44' E., 12.40 chs. dist.

METES AND BOUNDS SURVEY OF
TRACT 37, T. 30 N., R. 69 E.

State Selection, List No. 8, embracing the N½ SE¼ of sec. 33 containing 80 acres was approved February 8, 1890.

Control for the location of this parcel is based on the original ¼ sec. cor. of secs. 33 and 34, and the point for the original S. 1/16 sec. cor. of secs. 33 and 34. AP 1 and AP 4 of the tract are identical with the above corners, respectively. AP 2 was established 40.00 WEST of AP 1. The W. and S. boundaries of the tract were established parallel to the E. and N. boundaries, respectively.

Angle point 1, Tract 37, identical with the original ¼ sec. cor. of secs. 33 and 34, T. 30 N., R. 69 E., monumented with a limestone, 15x12x4 ins., firmly set in the ground, mkd. ¼ on the W. face; this cor. will now function for angle point 1, Tract 37, only.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

TR-37 | S 34
AP-1 |

1971

bury the original corner stone alongside the iron post.

Thence, WEST.

Ascend 20 ft. over E. slope.