

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH,  
THROUGH R. 68 E., MDM, NEVADA

CHAINS	
	<p>The standard cor. of secs. 35 and 36, T. 31 N., R. 68 E., monumented with an iron post, 2 ins. diam., showing 22 ins. above ground and firmly set in a mound of stone, with brass cap mkd.</p>
	<p style="text-align: center;">S C T31N R68E <u>S 35   S 36</u></p>
	<p style="text-align: center;">1938</p>
	<p>S. 88° 44' E., along the S. bdy. of sec. 36.</p>
	<p>Over mountainous land, through scattered timber and undergrowth; asc. 80 ft. over WNW. slope.</p>
29.50	<p>Ridge, bears NE. and SW.; desc. 100 ft. over E. slope.</p>
39.92	<p>The standard <math>\frac{1}{4}</math> sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., showing 8 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">S C <u><math>\frac{1}{4}</math> S 36</u></p>
	<p style="text-align: center;">1938</p>
	<p>raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p>S. 88° 44' E., beginning new measurement.</p>
	<p>Over mountainous land, through scattered timber and undergrowth; desc. 120 ft. over E. slope.</p>
12.20	<p>Wash, 20 lks. wide, 3 ft. deep, drains NE.; asc. 70 ft. over W. slope.</p>
30.00	<p>Ridge, bears WSW. and NE.; desc. 50 ft. over SE. slope.</p>
37.30	<p>Trail road, bears NE. and SW.; desc. 10 ft.</p>
40.01	<p>The standard cor. of Tps. 31 N., Rs. 68 and 69 E., monumented with an iron post, 3 ins. diam., showing 8 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">S C T31N R68E R69E <u>S 36   S 31</u></p>
	<p style="text-align: center;">1936</p>
	<p>from which the original bearing tree</p>
	<p>A pinon, 4 ins. diam., bears N. 63° W., 43<math>\frac{1}{4}</math> lks. dist., mkd. BT.</p>