

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH,  
THROUGH R. 69 E., MDM, NEVADA

CHAINS	
21.00	Telephone line, bears N. $3\frac{1}{4}^{\circ}$ E. and S. $3\frac{1}{4}^{\circ}$ W.
23.10	Abandoned U. S. Highway No. 50, bears N. $3\frac{1}{4}^{\circ}$ E. and S. $3\frac{1}{4}^{\circ}$ W.
40.01	<p>The standard cor. of secs. 35 and 36, monumented with an iron post, 2 ins. diam., showing 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S C T31N R69E <u>S 35   S 36</u></p> <p style="text-align: center;">1936</p> <p>raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.</p> <p>Land, rolling. Soil, sandy clay and gravel. Timber, none. Undergrowth, sagebrush, greasewood and bunchgrass.</p>
40.01	<p>S. <math>88^{\circ} 35'</math> E., along the S. bdy. of sec. 36.</p> <p>Over nearly level land, through scattered undergrowth; desc. 50 ft. over gradual E. slope.</p> <p>The standard <math>\frac{1}{4}</math> sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., showing 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S C <u><math>\frac{1}{4}</math> S 36</u></p> <p style="text-align: center;">1936</p> <p>raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. <math>88^{\circ} 37'</math> E., beginning new measurement.</p> <p>Over nearly level land, through scattered undergrowth; desc. 70 ft. over gradual E. slope to the sec. cor.</p>
1.10	Wash, 40 lks. wide, 2 ft. deep, drains NE.
32.90	Wash, 40 lks. wide, 1 ft. deep, drains NE.
40.01	<p>The standard cor. of Tps. 31 N., Rs. 69 and 70 E., monumented with an iron post, 3 ins. diam., showing 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S C T31N R69E R70E <u>S 36   S 31</u></p> <p style="text-align: center;">1936</p> <p>raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.</p>