389

DEPENDENT RESURVEY OF THE SIXTH STANDARD PARALLEL NORTH, THROUGH R. 70 E., MDM, NEVADA

CHAINS	
40.01	The standard cor. of secs. 33 and 34, monumented with an iron post, 2 ins. diam., showing 2 ins. above ground, with brass cap mkd. S C T31N R70E S 33|S 34 1936 raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor., and set a steel fence post, 5 ft. long, 2 ft. in the ground alongside the iron post. Land, level. Soil, sandy clay and gravel. Timber, none. Undergrowth, sagebrush, greasewood and bunchgrass.
	S. 88° 40' E., along the S. bdy. of sec. 34. Over nearly level land, through scattered undergrowth; desc. 40 ft. over rolling E. slope.
40.01	The standard ¼ sec. cor. of sec. 34, monumented with an iron post, 1 in. diam., showing 6 ins. above ground, with brass cap mkd. S C ¼ S 34 1936 raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.
	S. 88° 37' E., beginning new measurement. Over level land, through scattered undergrowth.
4.90	Old railroad bed, bears NNE. and SSW.
7.48	The standard closing corner of Tps. 30 and 31 N., R. 70 E., monumented with an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record. This monument now becomes an amended monument and the brass cap is remarked as follows: A M 1971
7.55	Intersect the Nevada-Utah State Line. Point for the standard closing cor. of Tps. 30 and 31 N., R. 70 E. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.