

INDEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 30 N., R. 70 E., MDM, NEVADA

CHAINS

from this corner

The standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 31 N., R. 70 E., monumented with an iron post, 1 in. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, through R. 70 E., resurveyed concurrently under this same group, bears S. $88^{\circ} 31'$ E., 12.07 chs. dist.

Land, gently rolling.

Soil, sandy clay and gravel.

Undergrowth, sagebrush, greasewood and bunchgrass.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 5, on the Sixth Standard Parallel North and at midpoint on the N. bdy. of sec. 5.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 5
T30N R70E

1971

raise a mound of stone, 4 ft. base, 2 ft. high, S. of cor.

from this corner

The standard cor. of secs. 31 and 32, T. 31 N., R. 70 E., monumented with an iron post, 2 ins. diam., set, mkd. and witnessed as described in the field notes of the dependent resurvey of the Sixth Standard Parallel North, through R. 70 E., resurveyed concurrently under this same group, bears S. $88^{\circ} 30'$ E., 12.14 chs. dist.

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the independent resurvey of the north boundary of T. 29 N., R. 70 E., executed under Group No. 463, in 1970.

N. $0^{\circ} 02'$ E., bet. secs. 33 and 34.

Over rolling land, through scattered undergrowth; desc. 20 ft. over N. slope.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.