

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 34 N., R. 42 E., MDM, NEVADA

CHAINS	
	<p style="text-align: center;">T34N R42E  <math>\frac{1}{4}</math> <math>\frac{S\ 36}{S\ 1}</math>            T33N</p> <p style="text-align: center;">1972</p> <p>bury the marked stone and set a steel fence post, 6 ft. long, 1 ft. in the ground, alongside the iron post.</p> <hr/> <p>S. 89° 57' W., beginning new measurement.</p> <p>Over mountainous land; asc. 170 ft. over E. slope.</p>
34.00	Spur, slopes ENE.; asc. 20 ft. over S. slope.
40.44	<p>The cor. of secs. 1, 2, 35 and 36, monumented with the original basalt stone, 16x8x6 ins., mkd. with 1 notch on the E. edge and 5 notches on the W. edge.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T34N R42E  <math>\frac{S\ 35\   S\ 36}{S\ 2\   S\ 1}</math>            T33N</p> <p style="text-align: center;">1972</p> <p>bury the marked stone and set a steel fence post, 6 ft. long, 8 ins. in the ground, alongside the iron post.</p> <hr/> <p>N. 89° 48' W., bet. secs. 2 and 35.</p> <p>Over mountainous land, through shadscale and sagebrush; asc. 80 ft. along S. slope.</p>
9.50	Ravine, drains SE.; asc. 40 ft. over N. slope.
20.00	Spur, slopes SE.; desc. 20 ft. over SW. slope.
24.70	Ravine, drains SE.; asc. 150 ft. over SE. slope.
38.30	Ridge, bears NNE. and SSW.; desc. 10 ft. over W. slope.
40.00	<p>The ¼ sec. cor. of secs. 2 and 35, monumented with the original basalt stone, 14x10x6 ins., mkd. ¼ on the N. face, firmly set in the ground.</p> <p>At the corner point</p>