

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 34 N., R. 42 E., MDM, NEVADA

CHAINS	
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 12 ins. above ground and in a collar of stone, with a mound of stone, 4 ft. base, 3 ft. high, W. of cor., with brass cap mkd.</p> <p style="text-align: center;">T34N R42E R43E S 25 S 30 S 36 S 31</p> <p style="text-align: center;">1971</p> <p>S. 89° 05' W., bet. secs. 25 and 36.</p> <p>Over mountainous land, through shadscale; asc. 20 ft. over NE. slope.</p>
12.40	Trail road, parallels power line.
14.00	Center of double pole power line, bears S. 51¼° E. and N. 51¼° W.
18.40	Ravine, drains NE.; asc. 70 ft. over NE. slope.
38.76	Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T34N R42E S 25 ¼ ——— S 36</p> <p style="text-align: center;">1972</p> <p>set a steel fence post, 6 ft. long, 2 ft. in the ground, alongside the iron post.</p> <p>Ascend 120 ft. over NE. slope.</p>
67.40	Spur, slopes ENE.; desc. 30 ft. over NNW. slope.
70.10	Ravine, drains ENE.; asc. 40 ft. over NE. slope.
75.10	Ravine, drains ENE.; asc. 70 ft. over NE. slope.
77.52	The cor. of secs. 25, 26, 35 and 36.
	<p>N. 0° 35' W., bet. secs. 25 and 26.</p> <p>Over mountainous land, through shadscale; desc. 20 ft. over NW. slope.</p>